

Product & Service Information "Brand Verification"

TECHNICAL

PACKING & LOADING

Thick	No of shts	Volume	Net Weight
3mm CG	150	1.35M3	600 kgs
5mm CG	095	1.42M3	485 kgs
5mm LG	095	1.42M3	485 kgs
6mm CG	090	1.42M3	490 kgs
6mm LG	090	1.42M3	490 kgs
8mm CG	055	1.32M3	500 kgs
8mm LG	055	1.32M3	500 kgs
16mm CG	030	1.45M3	540 kgs
Packing	approx:	36 kgs	

- Bottom blocks for 4 point lifting access
- Top and Bottom protection sheets
- Plastic wrapped
- Corner protection
- Plywood 4 sides LCL
- 7 strapping points
- Markings O/N, Product Type, Production Date & No, Pallet No, Client Name...



LOADING

20FT CONTAINERS	12 PALLETS
40FT CONTAINERS	24 PALLETS
40FT HIGH CUBE	33 PALLETS
LCL	PART LOADS
PACKING MATERIALS	ISPM 15

Sheet size:

1220mm X 2440mm CROSS GRAIN

Thickness:

3mm, 5mm, 8mm, 12mm & 16mm
4mm, 6mm, 7mm, 9mm, 10mm, 14mm
on request

Bending Radius: 3mm/3cm, 5mm/5cm, 6mm/6cm, 8mm/8cm
12mm/15cm & 16mm/20cm (Approx)

No of plies: 3mm, 5mm, 6mm & 8mm - 3 ply
12mm & 16mm - 5 ply

Density:

300kgs - 320kgs / M3 @ 12% MC

Weight per sheet: 3mm - 4kgs, 5mm - 5.1kgs, 6mm - 6.3kgs
8mm - 9.1kgs, 12mm - 14kgs & 16mm - 18kgs

Screw holding: 900 Newton

Nail holding: 55 Newton

Internal bond: 1.2 MPA

Modulus of rupture: 1.5 MPA

(Perpendicular to grain compression)

Modulus of elasticity: 85 MPA

(Perpendicular to grain compression)

Resistance - shearing 2.3 MPA

ADHESIVES : EXTERIOR 1 PF RESIN
MOISTURE & WEATHER PROTECTION
TESTED TO EUROPEAN STANDARD
EMISSIONS LOW EMISSIONS

HARMONIZED STANDARDS

VENEERS FACE A/B PRE-SANDED 120-150 GRIT
SUPER FORMTM EDGE STAMPED AND LABELED
CG or LG+Thickness No of sheets. Every pallet is labeled CE certified

Super formTM sheets are edged stamped
"Brand Verification"