

**DECLARATION OF PERFORMANCE
MEDITE PREMIER FR EUROCLASS B**

Reference Number: **DOP20REV6**

MEDITE EUROPE DAC

Redmondstown

Clonmel

County Tipperary

Ireland


| Product Type | Intended Use | AVCP* | Notified Body Reference |
|---|---|-------|---------------------------------------|
| L-MDF | Internal use as non-structural components in dry conditions | 1 | Warrington Certification Limited 1121 |
| *Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011 | | | |

Declared Performance

| Essential characteristics | Performance | | Harmonised technical specification |
|---|-------------|-----------|------------------------------------|
| Thickness Range | 12 to 19 | >19 to 25 | EN 13986:2004+A1:2015 |
| Internal bond (N/mm ²) | 0.45 | 0.45 | |
| Swelling in thickness (24hrs) % | 14 | 12 | |
| Release of formaldehyde | E1 | E1 | |
| Reaction to fire | B-s1,d0 | B-s1,d0 | |
| Water vapour permeability μ | NPD | NPD | |
| Airborne sound insulation (surface mass) (R) | NPD | NPD | |
| Sound absorption Frequency range 250Hz to 500Hz (α) | NPD | NPD | |
| Sound absorption Frequency range 1000Hz to 2000Hz (α) | NPD | NPD | |
| Thermal conductivity λ | NPD | NPD | |
| Biological Durability | Use Class 1 | | |
| Release (content) of pentachlorophenol (PCP) | ≤5ppm | ≤5ppm | |

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 28/05/2020